

## Major Applications

Next generation Nano - Ceramic Coatings for,

- ✓ Clear automotive finishes
- ✓ Automotive PPF & vinyl films
- ✓ Aircraft protective applications
- ✓ Marine protective applications
- ✓ Both ferrous and non-ferrous metals and alloys
- ✓ Corrosion resistant applications

# ONYX

COATING



5 YEARS WARRANTY

# ONYX

COATING

## QUARTZ PRO 9H

9H Nano Coating Product with super hardness and silky touch that stays for 5 years

## Quartz Pro Coating 9H

### Product Overview

Quartz Coating Series is the Latest generation ceramic coatings suitable for paint, plastic, metals, aluminums. The coatings can be easily applied by using sponge or cloth applicators. Our patented technology allows the coatings to deeply penetrate the surface and form a secure and tight bond, thus creating a thick ceramic protective layer. The flashing time for the product varies according to the temperature of the surface and the surrounding and humidity levels. We highly recommend finding the correct application time before usage. The initial cure will be ready within 2~5 hours after application, the full cure will take 14 days in room temperature, build-up time: 4~6 days.

This product has outstanding chemical resistance, gloss, hardness, sleekness, and water repellency.

### Technical Data

→ APPEARANCE	Clear
→ FINISH	Outstanding Gloss
→ CHEMICAL RESISTANCE	Grade 5 (Min 0 Max 5)
→ COVERAGE	108 sqft / 1.8 ounce (50 ml)
→ SHELF LIFE	12 months from manufacturing date when unopened and stored dry at 18° C (64° F) to 23° C (73° F)
→ DURABILITY	Up to 5 Years with condition of proper maintenance
→ PENCIL HARDNESS	9 H
→ FILM THICKNESS	600~800nm
→ SALT SPRAY (ASTM B117)	@ 35° C (95° F), 5% salt concentration, > 400 hrs to first sign corrosion
→ ADHESION CROSS - CUT TAPE (ASTM D33)	5b (0%, none)
→ MANDREL BEND (ASTMD522)	0% @ 180° rotation
→ IMPACT (ASTM D2794)	80/80 in/lbs
→ WATER REPELLENCY	110° at 20 µL, glass
→ OIL REPELLENCY	80° at 20 µL, glass
→ ROLL-OFF ANGLE	4~7° at 20 µL, glass